
CONTRACT NO. 60D20

					, ,,,,,,	
F.A.U. RTE.	SECTION	C	OUNT	′	TOTAL SHEETS	SHEET NO.
332	2007-037	TS C	:00K/\	VILL	34	24
STA. TO STA.						
FED. ROAD DIST. NO.		ILLINOIS	FED.	AID	PROJECT	

D-91-343-07



TYPICAL APPLICATIONS

Utility operations Culvert extensions Side slope changes Guardrall installation and maintenance Delineator installation Landscaping operations Shoulder repair Sign installation and maintenance

SYMBOLS



O Cone, drum or barricade

① When the work operation exceeds one hour, cones, drums or barricades shall be placed at 8 m (25') centers for L/3 distance, and at 15 m (50') centers through the remainder of the work area.

This Standard is used where any vehicles, equipment, workers or their activities will encroach in the area 4.5 m (15′) to 600 (24) from the edge of pavement.

Calculate L as follows:

SPEED LIMIT

FORMULAS

70 km/h (40 mph) Metric (English) L= WS 2 150 L= <u>WS 2</u>

80 km/h (45 mph)

or less:

or greater: L=0.65(W)(S) L=(W)(S)

W = Width of offset in meters (feet).

S = Normal posted speed km/h (mph).

All dimensions are in millimeters (inches) unless otherwise shown.

OFF-RD OPERATIONS, 2L, 2W, 4.5 m (15') TO 600 mm (24") FROM PAVEMENT EDGE

STANDARD 701006-02

	REVISIONS		ILLINOIS DEPARTMENT OF TRANSPORTATION					
	NAME	DATE	TELINOIS D	CI AIT I WILLIAM OF 117	ANSFURTATION			
	· I							
				DISTRICT OF	VF			
			EXP	RESSWAY LANE				
				DETAILS				
TOTALO TALO				:				
RING, INC.			CON F VERT.					
:2			SCALE: HORIZ.		DRAWN BY BL			
			DATE 11/26/07		CHECKED BY ER/TC			

DATE = 11/26/2007
NAME = *FILEL*
SCALE = *SCALE*
NAME = *ILAME)